
DATASHEET



General data

Outdoor Suitable for direct burial, duct or shaft installation
Primary cabling (Campus), Backbone
PE jacket black , non-metallic, longitudinal water tight
UV resistant, rodent resistant
Central/Loose tubes, 250µm coating. The cable diameter can vary.

Characteristics and advantages of Trunk cables:
• 2 up to 48 fibers per cable (other Trunks available on request)
• Pre-assembled, polished and factory-tested
• Both-sided assembled with stepped plug whips
• Ready to use, no need for expensive splice- and measuring equipment
• With Premium or Standard cable divider at customers choice
• Attenuation protocol for each assembled connector included in delivery
• All possible combinations of connectors like LC, E2000®, SC and ST available
• Identification with cable markers
• Delivery depending on length and type: one way drum or cable ring

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Number of connectors connection 1	Number of connectors connection 2	Number of fibres
O8325.1ADQOM4		1.0 m	8	8	8

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION