



# DATASHEET


## Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,200m Dca LSZH











### General data

**EFB sets standards in high quality**

For many years, EFB has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

**Advantages:**
**Fast delivery:** standard lengths up to 200 m in standard quantities available from stock
**Reduction of installation costs:** No splicing and assembly equipment required
**Reduced installation time:** cable ready for direct installation
**Traceable quality:** cable with serial number and measurement protocol

**Performance features:**
4, 8 or 12 fibers per cable
Fibre class OS2, OM3 or OM4
Factory production, polishing and function test

**This datasheet was created automatically on 19-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,200m Dca LSZH

Double-sided assembled stepped cable whips (longest length 1 m)
Identification of the remote individual cables with cable markers (numbers)
Serial number on the cable
Attenuation protocol for each individual fiber is provided
Delivery on both sides with fabric hose as drawing-in tube
Delivery up to 40 m in polybag, from 50 m on disposable drum
Raw cable: CPR-Class Dca
Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

### Tekniske egenskaber

### Available variants

| ArtNr. | Bezeichnung | Length | Outer diameter sheath single fibre | Length tolerance |
|---|---|---|---|---|
| O8341S10OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,10m Dca LSZH | 10 m | 2 mm | ±5 % |
| O8341S20OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,20m Dca LSZH | 20 m | 2 mm | ±5 % |
| O8341S30OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,30m Dca LSZH | 30 m | 2 mm | ±5 % |
| O8341S40OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,40m Dca LSZH | 40 m | 2 mm | ±5 % |
| O8341S50OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,50m Dca LSZH | 50 m | 2 mm | ±5 % |
| O8341S60OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,60m Dca LSZH | 60 m | 2 mm | ±5 % |
| O8341S70OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,70m Dca LSZH | 70 m | 2 mm | ±5 % |
| O8341S80OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,80m Dca LSZH | 80 m | 2 mm | ±5 % |
| O8341S90OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,90m Dca LSZH | 90 m | 2 mm | ±5 % |
| O8341S100OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,100m Dca LSZH | 100 m | 2 mm | ±5 % |
| O8341S110OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,110m Dca LSZH | 110 m | 2 mm | ±5 % |
| O8341S120OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,120m Dca LSZH | 120 m | 2 mm | ±5 % |
| O8341S130OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,130m Dca LSZH | 130 m | 2 mm | ±5 % |

**This datasheet was created automatically on 19-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,200m Dca LSZH

| | | | | |
|---|---|---|---|---|
| O8341S140OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,140m Dca LSZH | 140 m | 2 mm | ±5 % |
| O8341S150OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,150m Dca LSZH | 150 m | 2 mm | ±5 % |
| O8341S160OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,160m Dca LSZH | 160 m | 2 mm | ±5 % |
| O8341S170OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,170m Dca LSZH | 170 m | 2 mm | ±5 % |
| O8341S180OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,180m Dca LSZH | 180 m | 2 mm | ±5 % |
| O8341S190OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,190m Dca LSZH | 190 m | 2 mm | ±5 % |
| O8341S200OM4 | Trunk cable U-DQ(ZN)BH OM4 12G (1x12) SC-SC,200m Dca LSZH | 200 m | 2 mm | ±5 % |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION