
DATASHEET

Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,200m Dca LSZH



General data

EFB sets standards in high quality

For many years, EFB has been offering individual fiber optic assemblies from its own production for insertion into cable ducts and shafts. Now there is also a standard line, which is kept in stock. These are pre-assembled trunk cables with SC connectors in the OS2, OM3 and OM4 categories. The stocked lengths can be found in the overview below.

Advantages:
Fast delivery: standard lengths up to 200 m in standard quantities available from stock
Reduction of installation costs: No splicing and assembly equipment required
Reduced installation time: cable ready for direct installation
Traceable quality: cable with serial number and measurement protocol

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,200m Dca LSZH

Performance features:
4, 8 or 12 fibers per cable
Fibre class OS2, OM3 or OM4
Factory production, polishing and function test
Double-sided assembled stepped cable whips (longest length 1 m)
Identification of the remote individual cables with cable markers (numbers)
Serial number on the cable
Attenuation protocol for each individual fiber is provided
Delivery on both sides with fabric hose as drawing-in tube
Delivery up to 40 m in polybag, from 50 m on disposable drum
Raw cable: CPR-Class Dca
Length of the draw-in tube of 130cm, diameter: 4 fiber approx. 10mm, 8 fiber approx. 15mm, 12 fiber approx. 20mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Outer diameter sheath single fibre	Length tolerance
O8341S10OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,10m Dca LSZH	10 m	2 mm	±5 %
O8341S20OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,20m Dca LSZH	20 m	2 mm	±5 %
O8341S40OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,40m Dca LSZH	40 m	2 mm	±5 %
O8341S60OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,60m Dca LSZH	60 m	2 mm	±5 %
O8341S80OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,80m Dca LSZH	80 m	2 mm	±5 %
O8341S100OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,100m Dca LSZH	100 m	2 mm	±5 %
O8341S110OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,110m Dca LSZH	110 m	2 mm	±5 %
O8341S120OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,120m Dca LSZH	120 m	2 mm	±5 %
O8341S140OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,140m Dca LSZH	140 m	2 mm	±5 %
O8341S160OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,160m Dca LSZH	160 m	2 mm	±5 %
O8341S170OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,170m Dca LSZH	170 m	2 mm	±5 %

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,200m Dca LSZH

O8341S180OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,180m Dca LSZH	180 m	2 mm	±5 %
O8341S190OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,190m Dca LSZH	190 m	2 mm	±5 %
O8341S200OS2	Trunk cable U-DQ(ZN)BH OS2 12E (1x12) SC-SC,200m Dca LSZH	200 m	2 mm	±5 %

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION