DATASHEET



General data

High Power PoE compliant to simplify deployment and installation
Multiple PoE repeaters can be deployed by daisy chain to extend range
Forwards Power over Ethernet (PoE) to remote device
Forwards 802.3af/at/bt High-Power PoE to remote device
Extends PoE connection for another 100 meters
No additional power supply required
Simple Plug and Play installation
Weatherproof IP66-rated housing
Maximum distance depends on the required Wattage of the PD.

Extend the reach of your Gigabit PoE-PlusPlus devices. For system integrators looking for a professional solution to help extend their Outdoor Gigabit PoE (802.3af/at/bt) network, the LevelOne POR-1311 is a perfect accessory to increase your network performance. Normal cable runs only reach 100 meters, but with the POR-1311 installers can extend the PoE network performance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining* multiple PoE repeaters. Simple yet durable, no software required. As a PoE-PlusPlus Repeater, the POR-1311 receives all power from the Power Sending Equipment (PSE), such as a PoE-PlusPlus switch. This means that the POR-1311 uses no external power supply, making it the most flexible option for systems integrators looking for an easy, affordable solution to increase the distance to attached devices on a network. The POR-1311 is compliant to IP66, and is therefore weatherproof from snow, rain, storms, desert heat, etc. For deployment in any harsh weather conditions, this PoE Repeater is up to the challenge. The POR-1311 is a long-ranged solution for deploying PoE IP Camera and any Gigabit Ethernet PoE PD powered by 802.3bt PSE.

General
Silver color

Features
Multiple PoE repeaters can be deployed by daisy chain to extend range

This datasheet was created automatically on 09-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Forwards Power over Ethernet (PoE) to remote devices
Forwards 802.3af/at/bt High-Power PoE to remote device
Extends PoE connection for another 100 meters

Miscellaneous
Cascadable No
Others
Operating humidity 5% RH ~ 90% RH
Operating temperature 0°C ~ 50°C
scope of delivery
POR-1311
Mounting kit
Quick Installation Guide

Physical Specifications
Dimensions (W x D x H) 270 x 200 x 70 mm
Product weight (kg) 1.08

System specifications
Indicator Power, PoE In, PoE Out
Fixing pole mount
Pin assignment and polarity 1/2 (+), 3/6 (-)
Port configuration RJ45
Standards IEEE 802.3 10Base-T, Ethernet
IEEE 802.3u 100Base-TX, Fast Ethernet
IEEE 802.3x Ethernet Flow Control
IEEE 802.3af Power over Ethernet (PoE)
IEEE 802.3at Power over Ethernet Plus (PoE+)

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
POR-1311		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION