

DATASHEET



General data

High Power PoE compliant to simplify deployment and installation
 Multiple PoE repeaters can be deployed by daisy chain to extend range
 Forwards Power over Ethernet (PoE) to remote device
 Forwards 802.3af/at/bt High-Power PoE to remote device
 Extends PoE connection for another 100 meters
 No additional power supply required
 Simple Plug and Play installation
 Weatherproof IP66-rated housing

Extend the reach of your Gigabit PoE-PlusPlus devices. For system integrators looking for a professional solution to help extend their Outdoor Gigabit PoE (802.3af/at/bt) network, the LevelOne POR-1321 is the perfect accessory to increase your network performance. As a 2-port repeater, it's now easier to add more devices to the network for greater deployment flexibility. Normal cable runs only reach 100 meters, but with the POR-1321 installers can extend the PoE network performance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining* multiple PoE repeaters. Simple yet durable, no software required. As a PoE-PlusPlus Repeater, the POR-1321 receives all power from the Power Sending Equipment (PSE), such as a PoE-PlusPlus switch. This means that the POR-1321 uses no external power supply, making it the most flexible option for systems integrators looking for an easy, affordable solution to increase the distance to attached devices on a network. The POR-1321 has 3 RJ-45 ports for easy deployment, 1 "IN" port that accepts the power and data for the first 100 meters, and 2 "OUT" ports for 1 PoE (power + data) and 1 non-PoE (data only) installation, that boosts and extends the device an additional 100 meters. On top it is compliant to IP66, and is therefore weatherproof from snow, rain, storms, desert heat, etc. For deployment in any harsh weather conditions, this PoE Repeater is up to the challenge. The POR-1321 is a long-ranged solution for deploying PoE IP Camera and any Gigabit Ethernet PoE PD powered by 802.3bt PSE.

* Maximum distance depends on the required Wattage of the PD.

General

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

Silver color

Features

Multiple PoE repeaters can be deployed by daisy chain to extend range
 Forwards Power over Ethernet (PoE) to remote devices
 Forwards 802.3af/High-Power PoE to remote device
 Extends PoE connection for another 100 meters

Miscellaneous

Cascadable No

Others

Operating humidity 5% RH ~ 90% RH
 Operating temperature 0°C ~ 50°C
 scope of delivery
 POR-1321
 Mounting kit
 Quick Installation Guide

Physical Specifications

Dimensions (W x D x H) 270 x 200 x 70 mm
 Product weight (kg) 1.08

System specifications

Indicator Power, PoE In, PoE Out
 Fixing pole mount
 Pin assignment and polarity 1/2 (+), 3/6 (-)
 Port configuration RJ45
 Standards IEEE 802.3 10Base-T Ethernet
 IEEE 802.3u 100Base-TX Fast Ethernet
 IEEE 802.3af PoE

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
POR-1321		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

