DATASHEET









General data

Extends a PoE connection up to 400 m over a single 2-wire cable Supports a full duplex data rate of up to 60 Mb/s Provides up to 15.4 W for Fast Ethernet PoE devices Indoor and outdoor devices available for various applications Integrated dip switch for speed adjustment.

Port configuration
Fast Ethernet RJ45: 1
RJ11: 1
802.3af PoE: 1

General
Color white

Others
Operating humidity 10% RH ~ 90% RH
Operating temperature 0°C ~ 50°C
Scope of delivery POT-1110
Quick Installation Guide

Physical Specifications
Product weight (kg) 0.8

This datasheet was created automatically on 31-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

System specifications
Output voltage DC 44-57V
Standards Auto-Detection for 10/100 Base-Tx and Half / Full duplex
Fully compatible with IEEE 802.3 / IEEE802.3u
Automatic MDIX FunctionAuto-Detection for 10/100 Base-Tx and Half / Full duplex
Fully compatible with IEEE 802.3 / IEEE802.3u
Automatic MDIX function

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. PoE power
POT-1110		15 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 31-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION