



# DATASHEET



## General data

The 19" network cabinet PRO 24 U from EFB-Elektronik in 600 x 1000 mm and black is designed for the structured installation of active and passive components in the network and IT environment. The bolted, completely pre-assembled frame combines high mechanical stability with practical equipment for demanding installations.

- Pre-assembled, bolted frame – Reduces assembly effort and provides a stable base under heavy loads.
- Perforated steel front and rear door with 270° door opening angle – Facilitates access during maintenance and supports hands-on operation in the rack.
- Baying-compatible design with cable entries in the roof and floor – Enables modular expansion and clean, flexibly adaptable cable routing.

The cabinet is designed as a 19" version in accordance with DIN 41494 and is intended for a maximum load capacity of 1000 kg. The passive ventilation supports operation in thermally non-critical environments, while the pre-punched, break-out openings in the roof and floor enable resealable cable routing. This is complemented by the mounting levels at the front and rear, the interchangeable door hinges and the front door with replaceable profile half-cylinder. The IP20 protection class and the earthing round off the concept for indoor use.

## Technical details

- Number of doors: 2
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



# DATASHEET

- Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated one-piece steel door
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 1-point quarter-turn latch with swing handle
- Rear door locking: 1-point quarter-turn latch with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

## Tekniske egenskaber

### Available variants

| ArtNr.          | Bezeichnung | Colour | Depth   | Front door locking system                         | Material front door | Material rear door | Max. load capacity | Number of height units | Rear door locking system                          | Width  | With glazed door | With vertical cable management |
|-----------------|-------------|--------|---------|---------------------------------------------------|---------------------|--------------------|--------------------|------------------------|---------------------------------------------------|--------|------------------|--------------------------------|
| PRO-2460TS.P1P2 |             | black  | 1000 mm | 1-point latch locking mechanism with swivel lever | Steel               | Steel              | 1000 kg            | 24 U                   | 1-point latch locking mechanism with swivel lever | 600 mm | False            | False                          |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

