

DATASHEET



Bild zeigt: PRO-4288TS.P2
Picture shows: PRO-4288TS.P2





Bild zeigt: PRO-4288TS.P2
Picture shows: PRO-4288TS.P2

General data

The 19" server cabinet PRO 24 U from EFB-Elektronik in 600 x 800 mm and black is designed for the structured installation of active and passive components in demanding network and IT environments. With a fixed frame, baying-compatible design and high mechanical load-bearing capacity, it is suitable for installations with high space and cabling requirements.

- Split perforated steel doors front and rear – Improve air permeability and support efficient expansion in the network and IT environment.
- Passive ventilation and cable entries in the roof and floor – Enable flexible routing without additional active cooling.
- Baying-compatible design with front and rear mounting levels – Facilitates modular construction and simplifies on-the-fly maintenance.

The cabinet is based on a screwed, completely pre-assembled frame and offers 24 U with a maximum load capacity of 1000 kg. The offset profile rails and the mounting levels at the front and rear create additional flexibility in terms of loading. The roof and floor each have two pre-punched, break-out openings. These can be closed again using 19" 2U blind plates. The floor is also equipped with a break-out opening type A. The front and rear doors open up to 270° and are locked with a 1-point quarter-turn latch with swing handle. The door hinges are replaceable. This means that access remains easy to control, even with dense loading.

Technical details

- Number of doors: 2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated steel door split
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 1-point quarter-turn latch with swing handle
- Rear door locking: 1-point quarter-turn latch with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management
PRO-2468TS.P2		black	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	1000 kg	24 U	1-point latch locking mechanism with swivel lever	600 mm	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

