

DATASHEET

19" Network Cabinet PRO 24U, 800x800 mm, RAL7035











General data

19" network cabinet according to DIN41494
Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismountable
Inside front and rear 4 x 19"profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable
Contrariwise numbering of rack units at the 19" profiles
Front door with window of certified safety glass (thickness 5 mm)
Front door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303
Profile half-cylinder exchangeable by customer (30/10 mm)
Rear door steel, 1-part, shortened, with 2 x latch locking (lock equal to door lock), 3U panel for cable entry below (690 x 67 mm)
Door stop for front and rear door possible left- or right-sided
Detachable side walls with 2 x latch locking (lock equal to the door lock)
Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X)
Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear
Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules
Internal earthing of all cabinet sections
Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 2 x M5 + 2 x 8 mm)
Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO 24U, 800x800 mm, RAL7035

Paint finish RAL7035, light grey
Protection degree IP20
Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key
Delivery in transport packaging on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
PRO-4788GR.G1SV	19" Network Cabinet PRO 47U, 800x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	47 U	2-point latch locking mechanism	800 mm	True	False	2186 mm	7035	2
PRO-4288GR.G1SV	19" Network Cabinet PRO 42U, 800x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	42 HE	2-point latch locking mechanism	800 mm	True	False	1963 mm	7035	2
PRO-3388GR.G1SV	19" Network Cabinet PRO 33U, 800x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	33 HE	2-point latch locking mechanism	800 mm	True	False	1563 mm	7035	2
PRO-2488GR.G1SV	19" Network Cabinet PRO 24U, 800x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	24 U	2-point latch locking mechanism	800 mm	True	False	1163 mm	7035	2
PRO-1888GR.G1SV	19" Network Cabinet PRO 18U, 800x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	18 U	2-point latch locking mechanism	800 mm	True	False	896 mm	7035	2
PRO-2488TS.G1SV		black	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	24 U	2-point latch locking mechanism	800 mm	True	False			

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION