
DATASHEET


19" Server Cabinet PRO 42U, 600x1000 mm, F+R 1-Part, RAL9005











General data

19" server cabinet according to DIN41494
Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismountable
Inside front and rear 4 x 19"profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable
Contrariwise numbering of rack units at the 19" profiles
Front and rear door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303
Profile half-cylinder exchangeable by customer (30/10 mm)
Door stop for front and rear door possible left- or right-sided
Detachable side walls with 2 x latch locking (lock equal to the door lock)
Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6
Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear
Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules
Internal earthing of all cabinet sections
Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 20 x M5 + 2 x 8 mm)
Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Server Cabinet PRO 42U, 600x1000 mm, F+R 1-Part, RAL9005

Paint finish RAL7035, light grey
Protection degree IP20
Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key
Delivery in transport packaging on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
PRO-2460TS.P1	19" Server Cabinet PRO 24U, 600x1000 mm, F+R 1-Part, RAL9005	black	1000 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	1360 kg	24 U	1-point latch locking mechanism with swivel lever	600 mm	False	False	1163 mm	9005	2
PRO-4260TS.P1	19" Server Cabinet PRO 42U, 600x1000 mm, F+R 1-Part, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1360 kg	42 HE	3-point rod locking mechanism with swivel lever	600 mm	False	False	1963 mm	9005	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION