

DATASHEET

19" Network Cabinet PRO-Modular 42U, 800x1000 mm, RAL9005









General data

19" rack frame according to DIN41494
Screwed steel sheet frame, completely pre-assembled, self-ventilated, dismountable
Inside front and rear 4 x 19"profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable
Contrariwise numbering of rack units at the 19" profiles
Delivery without front/rear door and side walls for modular, individual configuration
For installed front and rear door, door stop left or right-sided possible
Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6
Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear
Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules
Internal earthing of all cabinet sections
Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 2 x M5 + 2 x 8 mm)
Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)
Paint finish RAL7035, light grey / RAL9005, jet black
Protection degree IP20
Included accessories: 1 x brush, earthing bar pre-installed, 4 x levelling feet M12, 2 x key

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO-Modular 42U, 800x1000 mm, RAL9005

Delivery in transport packaging on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Material front door	Material rear door	Max. load capacity	Number of height units	Width	With vertical cable management	Height	RAL-number	Number of doors
PRO-4780GR.0D	19" Network Cabinet PRO-Modular 47U, 800x1000 mm, RAL7035	grey	1000 mm	Without	Without	1360 kg	47 U	800 mm	False	1963 mm	7035	-
PRO-4280GR.0D	19" Network Cabinet PRO-Modular 42U, 800x1000 mm, RAL7035	grey	1000 mm	Without	Without	1360 kg	42 HE	800 mm	False	1963 mm	7035	-
PRO-4280TS.0D	19" Network Cabinet PRO-Modular 42U, 800x1000 mm, RAL9005	black	1000 mm	Without	Without	1360 kg	42 HE	800 mm	False	1963 mm	9005	-

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION