



# DATASHEET

19" Server Cabinet PRO 42U, 800x1200 mm, F=1-P R=2-P, RAL9005



## General data

19" server cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, detachable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front and rear door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 20 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.



# DATASHEET

## 19" Server Cabinet PRO 42U, 800x1200 mm, F=1-P R=2-P, RAL9005

Paint finish RAL9005, jet black

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

### Tekniske egenskaber

### Available variants

| ArtNr.          | Bezeichnung                                                   | Colour | Depth   | Front door locking system                       | Material front door | Material rear door | Max. load capacity | Number of height units | Rear door locking system                        | Width  | With glazed door | With vertical cable management | Height  | RAL-number | Number of doors |
|-----------------|---------------------------------------------------------------|--------|---------|-------------------------------------------------|---------------------|--------------------|--------------------|------------------------|-------------------------------------------------|--------|------------------|--------------------------------|---------|------------|-----------------|
| PRO-4282TS.P1P2 | 19" Server Cabinet PRO 42U, 800x1200 mm, F=1-P R=2-P, RAL9005 | black  | 1200 mm | 3-point rod locking mechanism with swivel lever | Steel               | Steel              | 1360 kg            | 42 HE                  | 3-point rod locking mechanism with swivel lever | 800 mm | False            | False                          | 1963 mm | 9005       | 2               |
| PRO-4782TS.P1P2 | 19" Server Cabinet PRO 47U, 800x1200 mm, F=1-P R=2-P, RAL9005 | black  | 1200 mm | 3-point rod locking mechanism with swivel lever | Steel               | Steel              | 1360 kg            | 47 HE                  | 3-point rod locking mechanism with swivel lever | 800 mm | False            | False                          | 2186 mm | 9005       | 2               |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.

