


DATASHEET

19" Network Cabinet PRO 42U, 800x800 mm, RAL7035, Rear Door with Turning Handle



General data

19" network cabinet according to DIN41494

Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated, dismantlable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Front door with window of certified safety glass (thickness 5 mm)

Front and rear door with 3-point turning handle (up to 24U 1-point), lockable, incl. profile half-cylinder acc. to DIN18252 / EN 1303

Profile half-cylinder exchangeable by customer (30/10 mm)

Rear door steel, 1-part, in full cabinet height

Door stop for front and rear door possible left- or right-sided

Detachable side walls with 2 x latch locking (lock equal to the door lock)

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm, for 600 mm cabinet width cable entry only rear)

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

This datasheet was created automatically on 31-10-2026 . Technical changes reserved.



DATASHEET

19" Network Cabinet PRO 42U, 800x800 mm, RAL7035, Rear Door with Turning Handle

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 2 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

Paint finish RAL7035, light grey

Protection degree IP20

Included accessories: 1 x brush, 1 x set of captive nuts (PU 20 pcs.), earthing bar and earthing cables, 4 x levelling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
PRO-4288GR.G1S1	19" Network Cabinet PRO 42U, 800x800 mm, RAL7035, Rear Door with Turning Handle	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	42 HE	3-point rod locking mechanism with swivel lever	800 mm	True	False	1963 mm	7035	2
PRO-1888GR.G1S1		grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	18 U	1-point latch locking mechanism with swivel lever	800 mm	True	False			
PRO-2488GR.G1S1		grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	24 U	1-point latch locking mechanism with swivel lever	800 mm	True	False			

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 31-10-2026 . Technical changes reserved.

