


DATASHEET

Co-Location Rack PRO, 4 x 9U, 800x800 mm, F+R 1-Part Perforated, RAL9005



General data

19" network cabinet according to DIN 41494
 Steel sheet housing with screwed frame, completely pre-assembled, self-ventilated
 1, 2, 3 or 4 boxes for individual access
 Every box with independent cable ducts left and right for cable entry from top or bottom
 Inside front and rear 4 x 19" profiles per box (2 front, 2 rear), galvanised, step-less depth-adjustable
 Numbering of height units at the profiles
 Front- and rear doors steel, perforated, 1-part
 Doors with 1-point turning handle, lockable, incl. profile half-cylinder acc. to DIN 18252 / EN 1303
 Profile half-cylinder exchangeable by customer (30/10 mm)
 Door stop left and right-sided possible
 Detachable side walls with 2 x latch locking (lock equal to door lock)

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.



DATASHEET

Co-Location Rack PRO, 4 x 9U, 800x800 mm, F+R 1-Part Perforated, RAL9005

Side walls optional available perforated

Cabinets stackable side-by-side with and without side wall via baying set PRO-ANR01

Roof and bottom with covered cutouts for cable entry (left/right) and for accommodation of fan unit PRO-LFD02BT.xx

Intermediate bottoms sealed to side walls

Internal earthing of all cabinet parts

Max. load 600 kg

Paint finish RAL7035, light grey / RAL9005, jet black

Protection degree IP20

Included accessories: 1 x set of captive nuts (PU 20 pcs.), 4 x Leveling feet M12, 2 x key

Delivery in transport packaging on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Height	RAL-number	Number of doors	Suitable Fans	Number of Boxes
PRO-CL4-4288TS.P1	Co-Location Rack PRO, 4 x 9U, 800x800 mm, F+R 1-Part Perforated, RAL9005	Black	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	4 x 10 HE	1-point latch locking mechanism with swivel lever	800 mm	True	1963 mm	9005	8	PRO-LFD02BO.xx	4
PRO-CL2-4288GR.P1		grey	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	2 x 20 HE	1-point latch locking mechanism with swivel lever	800 mm	True					
PRO-CL2-4288TS.P1		Black	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	2 x 20 HE	1-point latch locking mechanism with swivel lever	800 mm	True					

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

