

DATASHEET

Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL7035



General data

Fan unit with integrated thermostat for use in roof of cabinets Co Location PRO
 Easy mounting at prepared opening B (210 x 380 mm) hanging at cabinet roof
 Power connector IEC C14, power cable please order separately, e.g. EK504.x
 Housing material steel sheet
 Paint finish RAL7035, light grey / RAL9005, jet black
 Scope of delivery: fan unit incl. thermostat, mounting accessories

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Noise Level	Number of fans	Width	Depth	RAL-number	Rated power	Volume flow, freeblowing	Noise emission
PRO-LFD02BT.GR	Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL7035	grey	48 dB	2	380 mm	210 mm	7035	44 W	330 m³/h	48 dB(A)
PRO-LFD02BT.TS	Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL9005	schwarz	48 dB	2	380 mm	210 mm	9005	44 W	330 m³/h	48 dB(A)

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.



DATASHEET

Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.

