

DATASHEET

Door for PRO 24U, W=600, Steel, 1-Part, LL, RAL7035,
Rear Door



General data

1-part steel door for 24U cabinets PRO in width 600 mm
For use as standard rear door, 3U panel for cable entry below the door
2 x latch locking (T3 / 1333, no profile half-cylinder)
Door opening angle 110° due to quick fasteners
Paint finish RAL7035, light grey / RAL9005, jet black
Delivery pre-assembled incl. all hinges, screws, 2 x key

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
--------	-------------	--	--------	--------	-------	------------	-------------	---

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Door for PRO 24U, W=600, Steel, 1-Part, LL, RAL7035, Rear Door

PRO-TUR246SV.GR	Door for PRO 24U, W=600, Steel, 1-Part, LL, RAL7035, Rear Door	600 mm	grey	1085 mm	600 mm	7035	True	True
-----------------	--	--------	------	---------	--------	------	------	------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

