DATASHEET

Door for PRO 24U, W=800, Glass, 1-Part, TH, RAL7035







General data

1-part glass door for 24U cabinets PRO in width 800 mm
Window made of certified safety glass (thickness 5 mm)
1-point-locking with turning handle and profile half-cylinder acc. to DIN18252 / EN1303 (PHC exchangeable by customer)
Door opening angle 180°
Paint finish (steel elements) RAL7035, light grey / RAL9005, jet black
Delivery pre-assembled incl. all hinges, screws, 2 x key

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	RAL-number	EMC-version	Version as door for disconnecting switch interlocking

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Door for PRO 24U, W=800, Glass, 1-Part, TH, RAL7035

PRO-TUR248G1.GR	Door for PRO 24U, W=800, Glass, 1-Part, TH, RAL7035	800 mm	grey	1085 mm	800 mm	7035	True	True
PRO-TUR248G1.TS	Door for PRO 24U, W=800, Glass, 1-Part, TH, RAL9005	800 mm	black	1085 mm	800 mm	9005	True	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION