

DATASHEET

Door for PRO 42U, W=600, Steel perf., 1-Part, TH,
RAL7035



General data

1-part steel door, perforated, for 42U cabinets PRO in width 600 mm

Perforation 80%

3-point-locking with turning handle and profile half-cylinder acc. to DIN18252 / EN1303 (PHC exchangeable by customer)

Door opening angle 180°

Paint finish RAL7035, light grey / RAL9005, jet black

Delivery pre-assembled incl. all hinges, screws, 2 x key

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Height	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
--------	-------------	---	--------	--------	-------	--------	------------	-------------	---

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



DATASHEET

Door for PRO 42U, W=600, Steel perf., 1-Part, TH, RAL7035

PRO-TUR426P1.GR	Door for PRO 42U, W=600, Steel perf., 1-Part, TH, RAL7035	600 mm	grey	1885 mm	600 mm	1963 mm	7035	True	True
PRO-TUR426P1.TS	Door for PRO 42U, W=600, Steel perf., 1-Part, TH, RAL9005	600 mm	schwarz	1885 mm	600 mm	1963 mm	9005	True	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

