

DATASHEET

Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL9005



General data

2-part steel door, for 42U cabinets PRO in width 800 mm
 3-point-locking with turning handle and profile half-cylinder acc. to DIN18252 / EN1303 (PHC exchangeable by customer)
 Door opening angle 180°
 Paint finish RAL7035, light grey / RAL9005, jet black
 Delivery pre-assembled incl. all hinges, screws, 2 x key

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	Height	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
PRO-TUR428S2.GR	Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL7035	800 mm	grey	1885 mm	800 mm	1963 mm	7035	True	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL9005

PRO-TUR428S2.TS	Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL9005	800 mm	black	1885 mm	800 mm	1963 mm	9005	True	True
-----------------	---	--------	-------	---------	--------	---------	------	------	------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

