DATASHEET

20mm aluminum Conduit 1250N flexible, 3.0m



General data

SALR Aluminium Ridig conduits
Heavy gauge
Al Mg Si 0,5 - F18
Standard lenght 3mtr
In accordance with IEC/EN 61386-21, IEC60423
Bendable
1250N
-45C - +250C
Corrosion Class 4 in accordance with EN61386

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Inner diameter	Material	Outer diameter
SALR16CH	16mm aluminum Conduit 1250N flexible, 3.0m	13.5 mm	Aluminium	16 mm
SALR20CH	20mm aluminum Conduit 1250N flexible, 3.0m	17.5 mm	Aluminium	20 mm
SALR25CH	30mm aluminum Conduit 1250N flexible, 3.0m	22.0 mm	Aluminium	25 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION