DATASHEET

EFB 1.25G SFP MM 850nm VCSEL 550m LC DDM, compatible to Cisco GLC-SX-MMD









General data

Gigabit SFP transceiver for multimode Gigabit high-speed data transmission in fiber optic networks. Compatible with GLC-SX-SMD and standard MSA SFP ports

Technical data
SFP transceiver with LC duplex connection
Hot-pluggable SFP
With digital diagnostic monitoring function
1310nm Fabry-Perot laser transmitter
LC duplex connection
Up to 550m on 50/125µm multimode fiber
Low EMC interference and good ESD protection
Temperature range 0 to +70°C
RoHS compliant

Area of application
1.25Gbit/s 1000Base-SX Ethernet
1.06 Gb/s Fiber Channel

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

EFB 1.25G SFP MM 850nm VCSEL 550m LC DDM, compatible to Cisco GLC-SX-MMD

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
SFP1000SX	EFB 1.25G SFP MM 850nm VCSEL 550m LC DDM, compatible to Cisco GLC-SX-MMD	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION