DATASHEET

25mm pvc rigid electrical conduit w. sleeve light gray turbo 320N



General data

UPRM conduit medium gauge, with molded-on coupler and sectional corrugation.
As standard color Light grey (RAL7035)
Standard lenght 3 meter
In accordance with IEC/EN 61386-21, IEC60423
Mechanical strenght = 750N
With Turbo Function

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Halogen free	Impact strength	Inner diameter	Material	Outer diameter
VRM16 HG	16mm pvc rigid electrical conduit w. sleeve light gray turbo 320N	grey	False	320 Newton	13 mm	PVC-U	16 mm
VRM20 HG	20mm pvc rigid electrical conduit w. sleeve light gray turbo 320N	grey	False	320 Newton	16.9 mm	PVC-U	20 mm
VRM25 HG	25mm pvc rigid electrical conduit w. sleeve light gray turbo 320N	grey	False	320 Newton	21.4 mm	PVC-U	25 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION