

DATASHEET



General data

Supports wireless transfer rates of up to 574Mbit/s (2.4GHz) or 2401Mbit/s (5GHz), 3000Mbit/s total
 Supports OFDMA and MU-MIMO
 Compatible with IEEE 802.11a/b/g/n/ac/ax and Wave 2 standards
 Built-in 2 x 2 MIMO antenna
 Multi-operation modes for different wireless applications
 Features up to 8 SSIDs to separate network traffic
 High power and reception sensitivity for optimal signal coverage and increased data throughput
 Supports WPA3 encryption
 Weatherproof IP-67 housing

The LevelOne WAB-8021 is a stand-alone AX3000 omni-directional outdoor dual-band Wi-Fi 6 PoE wireless access point that features Gigabit Ethernet ports and modern 802.11ax Wave 2 MU-MIMO (Multi-User Multiple-Input Multiple-Output), which allows multiple devices to simultaneously receive a high-bandwidth Wi-Fi signal and distribute the data more efficiently. It offers a combined speed of up to 2976 Mbps (574 Mbps in 2.4 GHz / 2401 Mbps in 5 GHz) and an outdoor omnidirectional transmission range of up to 100 m.

The device runs on the 2.4 and 5 GHz frequencies and offers support for the new WPA3 encryption. Of course, the WAB-8021 is also equipped with PoE, which eliminates the need for an additional power supply and makes installation easier. The advanced IP67 weatherproof design means the WAB-8021 is designed for outdoor use and can withstand rain, moisture, dust and snow. A fast, versatile and secure access point for a variety of outdoor networking needs.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

General

Color white

Features

- Web-Based GUI Configuration
- Multiple SSID (4 SSID for 2.4GHz, 4 SSID for 5GHz)
- Weatherproof IP67-rated housing

Miscellaneous

Frequency band 2.4/5GHz(Dual bands)

PoE Supported Yes

Wireless AP type Outdoor

Max Wi-Fi Data Rate 3000Mbps

Others

Approvals and Compliance

- CE
- RED
- RoHS

Operating humidity 10% RH ~ 90% RH

Operating temperature -20°C ~ 50°C

Storage humidity 5% RH ~ 95% RH

Storage temperature -20°C ~ 80°C

scope of delivery

- WAB-8021
- IP67 Plastic Waterproof Nylon Cable Gland
- Pole Mounting Hose Clamp (59-82mm)
- RJ45 Network Cable
- Quick Installation Guide
- Declaration of Conformity

performance

Reception sensitivity (dBm) 2.4 GHz radio:

- 802.11b / 1Mbps / RX Sensitivity: -90 (dBm)
- 802.11b / 11Mbps / RX Sensitivity: -85 (dBm)
- 802.11g / 6Mbps / RX Sensitivity: -90 (dBm)
- 802.11g / 54Mbps / RX Sensitivity: -72 (dBm)
- 802.11n HT20 / MCS0 / RX Sensitivity: -87 (dBm)
- 802.11n HT20 / MCS7 / RX Sensitivity: -70 (dBm)
- 802.11n HT40 / MCS0 / RX Sensitivity: -85 (dBm)
- 802.11n HT40 / MCS7 / RX Sensitivity: -68 (dBm)
- 802.11ax HE20 / MCS0 / RX Sensitivity: -83 (dBm)
- 802.11ax HE20 / MCS11 / RX Sensitivity: -60 (dBm)
- 802.11ax HE40 / MCS0 / RX Sensitivity: -83 (dBm)

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

- 802.11ax HE40 / MCS11 / RX Sensitivity: -56 (dBm)

5GHz radio:

- 802.11a HT20 / 6Mbps/ RX Sensitivity: -92 (dBm)
- 802.11a HT20 / 54Mbps/ RX Sensitivity: -72 (dBm)
- 802.11n HT20 / MCS0 / RX Sensitivity: -90 (dBm)
- 802.11n HT20 / MCS7 / RX Sensitivity: -70 (dBm)
- 802.11n HT40 / MCS0 / RX Sensitivity: -88 (dBm)
- 802.11n HT40 / MCS7 / RX Sensitivity: -68 (dBm)
- 802.11ac VHT20 / MCS0 / RX Sensitivity: -88 (dBm)
- 802.11ac VHT20 / MCS8 / RX Sensitivity: -70 (dBm)
- 802.11ac VHT40 / MCS0 / RX Sensitivity: -88 (dBm)
- 802.11ac VHT40 / MCS7 / RX Sensitivity: -68 (dBm)
- 802.11ac VHT80 / MCS0 / RX Sensitivity: -85 (dBm)
- 802.11ac VHT80 / MCS9 / RX Sensitivity: -58 (dBm)
- 802.11ax HE20 / MCS0 / RX Sensitivity: -88 (dBm)
- 802.11ax HE20 / MCS11 / RX Sensitivity: -62 (dBm)
- 802.11ax HE40 / MCS0 / RX Sensitivity: -86 (dBm)
- 802.11ax HE40 / MCS11 / RX Sensitivity: -58 (dBm)
- 802.11ax HE80 / MCS0 / RX Sensitivity: -84 (dBm)
- 802.11ax HE80 / MCS11 / RX Sensitivity: -55 (dBm)
- 802.11ax HE160 / MCS0 / RX Sensitivity: -82 (dBm)
- 802.11ax HE160 / MCS11 / RX Sensitivity: -51 (dBm)

Physical Specifications

Dimensions (W x D x H) 230 x 107 x 38 mm

Product weight (kg) 1.3

System specifications

Antenna 2 Built-in 5dBi MIMO 2.4GHz Omnidirectional Antenna, 2 Built-in 7dBi MIMO 5GHz Omnidirectional Antenna

EIRP (dBm) < 20 dBm

Encryption WPA2 Personal (AES), WPA3 Personal (AES)

Flash memory size 8 MB (SPI NOR), 128 MB (SPI NAND)

Frequency band 2.412 to 2.484 GHz, 5.18GHz to 5.825GHz

indicator

- Power
- System
- WIFI status

Fixing pole mount

Operating mode Gateway Mode, Repeater Mode, AP Mode

Port configuration 1 x LAN/WAN RJ45 ports (10/100/1000 Base-T)

Energy consumption < 16W

RAM size 512 MB

Standards

- IEEE 10BASE-T (IEEE 802.3)
- IEEE 100BASE-TX (IEEE 802.3u)
- IEEE 1000BASE-T (IEEE 802.3ab)
- IEEE 802.11a/b/g/n/ac/ax

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

● IEEE 802.3at Power over Ethernet

Wireless channels ● 2,412 to 2,484 GHz: CH 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 ● 5,150GHz to 5,850GHz : CH 36, 40, 44, 48 , 52, 56, 60, 64, 100, 104, 108, 116, 120, 124, 128, 132, 140, 149, 153, 157, 161, 165

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
WAB-8021		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

