

# DATASHEET

10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005



## General data

Steel sheet housing, self-ventilated, screwed, pre-assembled  
 Front door lockable, with latch, door opening angle 120°  
 Front door fully made of certified safety glass (4 mm)  
 Door stop left-sided  
 Roof and bottom with cable entry 145 x 70 mm  
 Inside 2 x 10" profile rails, depth adjustable in 60 mm raster  
 Max. mounting depth 230 mm (at delivery: ca. 170 mm)  
 Paint finish RAL7035, light grey / RAL9005, jet black / RAL9010, pure white  
 Width 312 mm, height 300 mm  
 Max. load 30 kg, protection degree IP20  
 Delivery incl. 1 x brush, 1 x plastic cover, key

## Tekniske egenskaber

## Available variants

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



# DATASHEET

## 10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005

| ArtNr.        | Bezeichnung                                                        | Colour | Depth  | Height | Max. Load | Number of height units | Width  | RAL-number |
|---------------|--------------------------------------------------------------------|--------|--------|--------|-----------|------------------------|--------|------------|
| WGB-1004GR.30 | 10" 4U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035 | grey   | 300 mm | 215 mm | 30 kg     | 4 U                    | 312 mm | 7035       |
| WGB-1004TS.30 | 10" 4U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005 | black  | 300 mm | 215 mm | 30 kg     | 4 U                    | 312 mm | 9005       |
| WGB-1004WS.30 | 10" 4U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9010 | white  | 300 mm | 215 mm | 30 kg     | 4 U                    | 312 mm | 9010       |
| WGB-1006GR.30 | 10" 6U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035 | grey   | 300 mm | 304 mm | 30 kg     | 6 U                    | 312 mm | 7035       |
| WGB-1006TS.30 | 10" 6U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005 | black  | 300 mm | 304 mm | 30 kg     | 6 U                    | 312 mm | 9005       |
| WGB-1006WS.30 | 10" 6U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9010 | white  | 300 mm | 304 mm | 30 kg     | 6 U                    | 312 mm | 9010       |
| WGB-1009GR.30 | 10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035 | grey   | 300 mm | 437 mm | 30 kg     | 9 U                    | 312 mm | 7035       |
| WGB-1009TS.30 | 10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005 | black  | 300 mm | 437 mm | 30 kg     | 9 U                    | 312 mm | 9005       |
| WGB-1009WS.30 | 10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9010 | white  | 300 mm | 437 mm | 30 kg     | 9 U                    | 312 mm | 9010       |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

