

# DATASHEET

## 19" 09U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035



### General data

19" Wall housing 1-part, type Flat Pack  
 Steel sheet housing screwable, not pre-assembled  
 Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic  
 Front door lockable, Door opening angle 120°  
 Door stop easy changeable (right/left)  
 Sidewalls not detachable  
 Roof prepared for mounting of 2 x single fans  
 Roof and bottom with cable entry 145 x 70 mm  
 Inside 2 x 19" profile rails, depth-adjustable, with lateral opening for cable routing  
 Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)  
 Width 535 mm, depth 450 / 600 mm  
 Max. load 80 kg (static, equally distributed)  
 Protection degree IP20  
 Incl. key  
 Delivery unassembled in 1 carton with handle

### Tekniske egenskaber

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



# DATASHEET

## 19" 09U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035

### Available variants

| ArtNr.        | Bezeichnung                                                          | Colour | Depth  | Height | Max. Load | Number of height units | Width  | RAL-number |
|---------------|----------------------------------------------------------------------|--------|--------|--------|-----------|------------------------|--------|------------|
| WGB-1906GR.45 | 19" 06U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035 | grey   | 450 mm | 304 mm | 80 kg     | 6 U                    | 535 mm | 7035       |
| WGB-1909GR.45 | 19" 09U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035 | grey   | 450 mm | 437 mm | 80 kg     | 9 U                    | 535 mm | 7035       |
| WGB-1912GR.45 | 19" 12U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035 | grey   | 450 mm | 571 mm | 80 kg     | 12 U                   | 535 mm | 7035       |
| WGB-1915GR.45 | 19" 15U Wall Housing Basic, Depth 450 mm, 1-Part, Flat Pack, RAL7035 | grey   | 450 mm | 707 mm | 80 kg     | 15 U                   | 535 mm | 7035       |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

