

DATASHEET











General data

New generation of wall cabinets, which gives the installer 100% flexibility during installation. The assembly process of the rack is done during the installation of hardware into the cabinet. All the coverplates (side, top&buttom + frontdoor), can be installed on the final end of the job. By ordering the back frame & cover parts separately, you can wait to order cover plates and front door until the colour is decided.

For 19” wall housing “X-Rack”, adjustable in depth: 400, 450, 500, 550 and 600 mm
100% Protection against installation error. Left/right side plates and roof/bottom plates are equal
Steel front door. Possibility to hinge left or right.
Adjustable door hinges to secure correct leveling of the door.
Secured sidewalls, only to be dismantled from front side behind the front door.
190x90 mm Cable entries in roof and bottom.
Mounting holes for single fan-units Art.-No 691664 in roof and bottom
Protection degree IP20
El-gavanised steel plates for higher quality
Side walls, roof and bottom plates El-galv. powder coating light grey or jet black
Quarter turn Lock with key. Can be exchanged to RUKO/ASSA with 699989 turning handles

General Data:

Type of ventilation Passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Active ventilation Mounting holes for 1 x fan unit in roof & bottom
Material & surface side plates El-galvanized Z275, steel plate, powder coating
Material & surface top&buttom El-galvanized Z275, steel plate, powder coating
Material & surface front door Steel plate door, powder coated, window of certified safety glass
Front door hinges Easy pin hinge for left or right side. Adjustable leveling of the door
Front door locking Quarter turn handle with standard key. Can be replaced by 699989 handle for RUK/ASSA
Side walls locking Protected against unauthorized access.
Degree of protection IP20
Width 600 mm
Height 9U: 500 mm / 12U: 600 mm / 15U: 766 mm
Depth Adjustable 400 mm, 450 mm, 500 mm, 550 mm, 600 mm
Packaging Package no.2 of 3: recycled cartonboard
Paint finish RAL7035, light grey / RAL9005, jet black

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width
WGX-O09GR.S		grey	400-600 mm	500 mm	60 kg	9 U	600 mm
WGX-O09TS.S		black	400-600 mm	500 mm	60 kg	9 U	600 mm
WGX-O12GR.S		grey	400-600 mm	600 mm	60 kg	12 U	600 mm
WGX-O12TS.S		black	400-600 mm	600 mm	60 kg	12 U	600 mm
WGX-O15GR.S		grey	400-600 mm	766 mm	60 kg	15 U	600 mm
WGX-O15TS.S		black	400-600 mm	766 mm	60 kg	15 U	600 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION