

Distribution box, Optical fiber

ORM5



Application

- Simple wall installation, Optical box for distribution or termination.
- Easy access due to hinged removable cover
- Lockable cover. (accessories)
- Indoor & Outdoor use, IP54
- Gradual cable gland located in the lower wall for for the cables with outside diameter 3 to 14mm.
- Gradual cable gland located in the lower wall for for the cables with outside diameter 3 to 10mm.
- 4 Prefabricated holes for dividable bushings capable to seal up to 2 patchcords or heavy duty sub-scribers cable
- Up to 2 x SC-D or 2 x E-2000-D or 2 x LC Quadro. (Total 8 pigtails)
- Hinged splice cassette supporting up to 12 fiber + 12 Heat shrink fusion splice protection's
- Ready to accommodate Gas blocker for the microtubes with varius diameter (5,7,10,12 & 14) at the input of the box.

Technical Specifications

Materiel :	PC + ABS Cylolac C2950-96235
Dimension :	235 x 156 x 45mm
Weight :	450 gr.
Color :	Light grey RAL7035
Temp:	-40°C to +70°C According to EN60068-2-14
Solar Radiation :	EN60068-2-5
Coverage degree :	IP54 in acc. to EN60529

Ordering Information

Order no.	EAN	Description	Color	Packsize
ORM5	5705721136728	Distr.box up to 12 fiber 2xSC-D or 2xLC Quadro	Light Grey	1 pcs
Accessories:				
ORM5 LUCK	5705721131600	Lock with Key for ORM5		1 pcs