

GEL-1061 Version: 1



10-Port-L2-Managed-Gigabit-Switch, 2 x SFP

The GEL-1061 is a L2 managed switches designed for the SMB market. The switches can be deployed indifferent target network topologies, from small to large. As well as IPv4 and IPv6 features. The GEL-1061 includes the best green-saving technologies (IEEE 802.3az and Green-Ethernet). Using the Energy Efficient Ethernet standard, the switch automatically decreases power usage when network traffic is low.

Key-features

- IEEE-802.1d/w/s Spanning Tree Protocol (STP) und Port-Spiegelung
- IEEE-802.3ad LACP für Auto-Port-Aggregation
- Port-basierende IEEE-802.1X-Authentifizierung über Zugriffliste (ACL) mit bis zu 512 Einträgen für eine einfache Netzwerksicherheit
- IP Multicast Filtering mittels IGMP Snooping V1/ V2/ V3
- unterstützen Port-basiertes VLAN, IEEE 802.1Q-VLAN-Tagging
- Unterstützt IPv4/IPv6
- IEEE 802.1p QoS mit 8 priority queues

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
 IEEE 802.3u 100-BASE-TX, Fast Ethernet
 IEEE 802.3ab 1000BASE-T, Gigabit Ethernet
 IEEE 802.3z 1000BASE-X, Gigabit Ethernet
 IEEE 802.1p Quality of Service (QoS)
 IEEE 802.1Q Virtual LANs (VLANs)
 IEEE 802.1D MAC Bridges
 IEEE 802.1d Standard Spanning Tree Protocol
 IEEE 802.1s Multiple Spanning Tree (MSTP)
 IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
 IEEE 802.3x Flow Control
 IEEE 802.3ad Link Aggregation Control Protocol (LACP)
 IEEE 802.3af Power over Ethernet (PoE)
 IEEE 802.3at Power over Ethernet Plus (PoE+)
 IEEE 802.3az Energy-Efficient Ethernet
 Link Layer Discovery Protocol (LLDP)
 Universal Plug and Play (UPnP)

Memory:

32MB

Pufferspeicher:

4.1Mbits

Connectors and Cabling:

8x RJ-45 10/100/1000BASE-T ports

2 x 100/1000Base-X SFP Slots

Taster:

Reset / Factory Default Button

Indikator:

Power; Link/Active

Transmission Method:

Store-and-Forward

Power Input:

100-240V AC, 50-60 Hz, Internal Power Supply

Power Consumption:

< 8W

Features

General:

Quality of Service (QoS):

8 hardware Priority Queues per port

Traffic classification based on IEEE 802.1p CoS

IPv4/IPv6 precedence/ type of service (ToS) / DSCP based

Rate Limiting - Ingress policer egress shaping and rate control

Spanning Tree:

Bridge Protocol Data Units (BPDU)

IEEE 802.1D MAC Bridges

IEEE 802.1d Spanning Tree Protocol (STP)

IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

Virtual Local Area Network (VLAN):

802.1Q tag-based VLAN - up to 4K VLANs and 4K VLAN IDs

Port-based VLAN

MAC-based VLAN

DHCP: DHCP Client; DHCP Relay (Layer 2)

IPv6:

IPv6 Ping / Trace / Telnet / Syslog / TFTP

IGMP:

IGMP v1/v2/v3 snooping; IGMP Queried; IGMP Filtering /Throtting

Port Mirroring:

One to One /One to Many

IEEE 802.3ad LACP Trunk

Security:

DDOS Protection

CPU Guard

Port Isolation

Port Mirror /Remote Mirror

Broadcast / Multicast / Unknown Storm Control

802.1X

ACL

Port Security

MAC Filter / MAC Authentication

AAA

IP Source Guard

SSH

Management:

System Password protection
NTP/SNTP
Dual Image /Configuration
Firmware upgrade /download (HTTP/TFTP/FTP)
RMON/ SNMP
Management Access (Console / SNMP/ Web / Telnet)
Memory Flash Log
Event /Error Log
DHCP v4/v6 Snooping
DHCP Snooping Option82

Ease of Use:

Dashboard

Performance**Backplane (Gbps):**

20Gbps

MAC-Adresstabelle:

8K

Datenrate:

10/100/1000Mbps

Weiterleitungsrate:

14.9 Mpps

Jumbo-Frames:

10K

Environment**Energieeffizienz:**

IEEE 802.3az Energy Efficient Ethernet:

- Automatically turns power off on RJ-45 port when detecting link down or Idle of client
- Cable length detection: Adjusts the signal strength based on the cable length
- Reduces the power consumption for cables shorter

Acoustic Noise:

0 dB (A)

Heat Dissipation:

27.297 (Btu/H)

Temperatur (°C):

0-50 C

Luftfeuchtigkeit (nicht kondensierend):

10-90%

Deployment:

desktop

Physical Specifications**Abmessungen (W x D x H mm):**

19.6x11.7x3.6mm

Gewicht:

Gross: 3007g

Net: 817g



Zuverlässigkeit

MTBF:

25 degreeC: 1284936 hrs

45 degreeC: 55390 hrs

Approval and Compliance

Zertifizierung:

CE classA, FCC, UL, VCCI, BSMI

Order Information

GEL-1061

Package Contents

GEL-1061

Stromkabel

19" Einbaurahmen

Quick Installation Guide

Ressource CD (Bedienungsanleitung)

Konsolenkabel