

Distribution box, Optical fiber

URM LL 48S

Application

The URM LL 48S optical distribution box is designed for placement of 48 optical splices indoor and outdoor. The distribution box may be complemented by a bracket, which enables it to be post-mounted.

- Maximum capacity is 48 splices - 4 cassette w 12 splices each
- Integrated fibre management by 4 x cable eye's
- Possibility of PLC splitter placement
- 4 x PG bushing for input/output cable
- Use only for fibers G657a,b
- Holders for cable tension element
- Lockable door



Technical Specifications

Materiel :	Distribution box: PC/ABS Bushings: PA6, TPV
Dimension :	250 x 373 x 69mm
Weight :	1,6 kg.
Color :	Light grey RAL7035
Temp:	-40°C to +70°C According to EN60068-2-14
Solar Radiation :	EN60068-2-5
Flameability :	UL94-V0
Impact protection degree :	IK10 to EN50102
Coverage degree :	IP54 in acc. to EN60529
Bushings :	4 x PG13,5
Enviroment :	Indoor & outdoor
Number of splices :	1 - 48 splices
Number of Couplers :	None

Ordering Information

Order no.	EAN	Description	Color	Packsize
URM LL 48S	5705721132089	Distribution box up to 48 fibers in/outdoor	Light grey	1 pcs.