

FO Pigtail ST/UPC MM 62,5/125 OM1, Semi tight

DK-O3313.2



Construction

- Semi Tight fiber—Easy strip.
- Pigtails for use in fiber optical box's and enclosures
- RoHS compliance
- 100% optical tested and labelled with Production Batch code.

Technical Specifications

- Insulation Resistance : $\geq 500 \text{ M}\Omega$
- Insertion Loss (IL) : $\text{IL} \leq 0,3 \text{ db}$
- Polishing : UPC (Ultra physical Contact)
- Colour of connector : Housing/boot: Metal/Black
- Colour of fiber : Primary Coating = Blue / secondary coating = Blue
- Connector ferrule : Zirconia
- Connector design : ST metal, Bajonet
- Cable OD : Outer diameter: 0,9 mm
- Material of jacket : LSZH, blue
- Core/Cladding diameter : 62,5/125 μm
- Stripability : One-step stripping length: minimum 1 mtr
- Weight : Brutto 50gr.
- Temp.range : $-40^{\circ}\text{C} - +85^{\circ}\text{C}$

Ordering Information

Order no.	Description	Color	Pack size
DK-O3313.2	Pigtail ST/UPC MM 62,5/125 OM1 2mtr.	Metal/Blue	4 pcs